



Designation: D5231 – 92 (Reapproved 2016)

Standard Test Method for Determination of the Composition of Unprocessed Municipal Solid Waste¹

This standard is issued under the fixed designation D5231; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This test method describes procedures for measuring the composition of unprocessed municipal solid waste (MSW) by employing manual sorting. This test method applies to determination of the mean composition of MSW based on the collection and manual sorting of a number of samples of waste over a selected time period covering a minimum of one week.

1.2 This test method includes procedures for the collection of a representative sorting sample of unprocessed waste, manual sorting of the waste into individual waste components, data reduction, and reporting of the results.

1.3 This test method may be applied at landfill sites, waste processing and conversion facilities, and transfer stations.

1.4 The values stated in inch-pound units are to be regarded as the standard. The values given in parentheses are for information only.

1.5 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.* For specific hazard statements, see Section 6.

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Terminology

2.1 Definitions:

2.1.1 *composite item*—an object in the waste composed of multiple waste components or dissimilar materials, such as

¹ This test method is under the jurisdiction of ASTM Committee D34 on Waste Management and is the direct responsibility of Subcommittee D34.03 on Treatment, Recovery and Reuse.

Current edition approved Sept. 1, 2016. Published September 2016. Originally approved in 1992. Last previous edition approved in 2008 as D5231 – 92 (2008). DOI: 10.1520/D5231-92R16.

disposable diapers, bi-metal beverage containers, electrical conductors composed of metallic wire encased in plastic insulation, etc.

2.1.2 *solid waste composition or waste composition*—the characterization of solid waste as represented by a breakdown of the mixture into specified waste components on the basis of mass fraction or of weight percent.

2.1.3 *sorting sample*—a 200 to 300-lb (91 to 136-kg) portion deemed to represent the characteristics of a vehicle load of MSW.

2.1.4 *unprocessed municipal solid waste*—solid waste in its discarded form, that is, waste that has not been size reduced or otherwise processed.

2.1.5 *waste component*—a category of solid waste, composed of materials of similar physical properties and chemical composition, which is used to define the composition of solid waste, for example, ferrous, glass, newsprint, yard waste, aluminum, etc.

3. Summary of Test Method

3.1 The number of samples to be sorted is calculated based on statistical criteria selected by the investigators.

3.2 Vehicle loads of waste are designated for sampling, and a sorting sample is collected from the discharged vehicle load.

3.3 The sample is sorted manually into waste components. The weight fraction of each component in the sorting sample is calculated from the weights of the components.

3.4 The mean waste composition is calculated using the results of the composition of each of the sorting samples.

4. Significance and Use

4.1 Waste composition information has widespread applications and can be used for activities such as solid waste planning, designing waste management facilities, and establishing a reference waste composition for use as a baseline standard in both facility contracts and acceptance test plans.

4.2 The method can be used to define and report the composition of MSW through the selection and manual sorting of waste samples. Where applicable, care should be taken to consider the source and seasonal variation of waste.

4.3 After performing a waste composition analysis, laboratory analyses may be performed on representative samples of waste components, or mixtures of waste components, for purposes related to the planning, management, design, testing, and operation of resource recovery facilities.

5. Apparatus

5.1 *Metal, Plastic, or Fiber Containers*, sufficient for storing and weighing each waste component, labeled accordingly. For components that will have a substantial moisture content (for example, food waste), metal or plastic containers are recommended in order to avoid absorption of moisture by the container and thus the need for a substantial number of weighings to maintain an accurate tare weight for the container.

5.2 *Mechanical or Electronic Weigh Scale*, with a capacity of at least 200 lb (91 kg) and precision of at least 0.1 lb (0.045 kg).

5.3 *Heavy-Duty Tarps, Shovels, Rakes, Push Brooms, Dust Pans, Hand Brooms, Magnets, Sorting Table, First Aid Kit, Miscellaneous Small Tools, Traffic Cones, Traffic Vests, Leather Gloves, Hardhats, Safety Glasses, and Leather Boots.*

6. Hazards

6.1 Review the hazards and procedures with the operating and sorting personnel prior to conducting the field activities.

6.2 Sharp objects, such as nails, razor blades, hypodermic needles, and pieces of glass, are present in solid waste. Personnel should be instructed of this danger, and they should brush waste particles aside while sorting rather than projecting their hands with force into the mixture. Personnel handling and sorting solid waste should wear appropriate protection, such as heavy leather gloves, dust masks, hardhats, safety glasses, and safety boots.

6.3 During the processes of unloading waste from collection vehicles and handling waste with heavy equipment, projectiles may issue from the mass of waste. The projectiles can include flying glass particles from breaking glass containers and metal lids from plastic and metal containers that burst under pressure when run over by heavy equipment. The problem is particularly severe when the waste handling surface is of high compressive strength, for example, concrete. Personnel should be informed of this danger and wear eye and head protection if in the vicinity of either the collection vehicle unloading point or heavy equipment, or both.

6.4 Select a location for the discharge of designated loads, manual sorting activities, and weighing operations that is flat, level, and away from the normal waste handling and processing areas.

6.5 Weigh storage containers each day, or more frequently, if necessary, in order to maintain an accounting of the tare weight.

6.6 Loss of mass from the sorting sample can occur through the evaporation of water. Samples should thus be sorted as soon as possible after collection.

6.7 Containers of liquids or other potentially dangerous wastes shall be put aside and handled by the crew chief.

7. Calibration

7.1 All weigh scale equipment shall be calibrated according to the manufacturer’s instructions. Take appropriate corrective action if the readings are different from those of the calibration weights.

8. Procedure

8.1 Secure a flat and level area for discharge of the vehicle load. The surface should be swept clean or covered with a clean, durable tarp prior to discharge of the load.

8.2 Position the scale on a clean, flat, level surface and adjust the level of the scale if necessary. Determine the accuracy and operation of the scale with a known (that is, reference) weight.

8.3 Weigh all empty storage containers and record the tare weights.

8.4 Determine the number of samples to be sorted. The determination is a function of the waste components to be sorted and the desired precision as applied to each component. Weights of 200 to 300 lb (91 to 136 kg) for sorting samples of unprocessed solid waste are recommended. The number of samples is determined using the calculational method described in 9.1.

8.5 A comprehensive list of waste components for sorting is given in Table 1. A description of some of the waste component categories is given in Table 2. Other waste components can be defined and sorted, depending on the purpose of the waste composition determination. The list in Table 1 is comprised of those components most commonly used to define and report the composition of solid waste. It is recommended that, at a minimum, the complement of left-justified categories in Table 1 be sorted. Similar breakdowns of solid waste composition are therefore available for purposes of comparison, if desired. Label the storage containers accordingly.

8.6 Vehicles for sampling shall be selected at random during each day of the one-week sampling period, or so as to be representative of the waste stream as agreed upon by the affected parties. With respect to the random selection of vehicles, any method is acceptable that does not introduce a bias into the selection. An acceptable method is the use of a random number generator. For a weekly sampling period of *k* days, the number of vehicles sampled each day shall be approximately *n/k*, where *n* is the total number of vehicle loads

TABLE 1 List of Waste Component Categories

Mixed paper	Other organics
High-grade paper	Ferrous
Computer printout	Cans
Other office paper	Other ferrous
Newsprint	Aluminum
Corrugated	Cans
Plastic	Foil
PET bottles	Other aluminum
HDPE bottles	Glass
Film	Clear
Other plastic	Brown
Yard waste	Green
Food waste	Other inorganics
Wood	

TABLE 2 Descriptions of Some Waste Component Categories

Category	Description
Mixed paper	Office paper, computer paper, magazines, glossy paper, waxed paper, and other paper not fitting the categories of newsprint and corrugated
Newsprint	Newsprint
Corrugated	Corrugated medium, corrugated boxes or cartons, and brown (kraft) paper (that is, corrugated) bags
Plastic	All plastics
Yard waste	Branches, twigs, leaves, grass, and other plant material
Food waste	All food waste except bones
Wood	Lumber, wood products, pallets, and furniture
Other organics/ combustibles	Textiles, rubber, leather, and other primarily burnable materials not included in the above component categories
Ferrous	Iron, steel, tin cans, and bi-metal cans
Aluminum	Aluminum, aluminum cans, and aluminum foil
Glass	All glass
Other inorganics/ non-combustibles	Rock, sand, dirt, ceramics, plaster, non-ferrous non-aluminum metals (copper, brass, etc.), and bones

to be selected for the determination of waste composition. A weekly period is defined as 5 to 7 days.

8.7 Direct the designated vehicle containing the load of waste to the area secured for discharge of the load and collection of the sorting sample.

8.8 Collect any required information from the vehicle operator before the vehicle leaves the discharge area. Direct the vehicle operator to discharge the load onto the clean surface in one contiguous pile, that is, to avoid gaps in the discharged load in order to facilitate collection of the samples.

8.9 Using a front-end loader with at least a 1-yd³ (0.765-m³) bucket, remove the material longitudinally along one entire side of the discharged load in order to obtain a representative cross-section of the material. The mass of material shall be sufficient to form a mass of material which, on a visual basis, is at least four times the desired weight of the sorting sample (that is, approximately 1000 lb (454 kg)). Mix, cone, and quarter the material, and select one quarter to be the sorting sample, using a random method of selection or a sequence agreed by all affected parties, for the purpose of eliminating or minimizing biasing of the sample. If an oversize item (for example, water heater) composes a large weight percent of the sorting sample, add a notation on the data sheet and weigh it, if possible. Unprocessed solid waste is a heterogeneous mixture of materials. Care must thus be taken during application of the procedures for sample collection in order to obtain a representative sample.

8.10 One sorting sample is selected from each collection vehicle load designated for sampling. All handling and manipulation of the discharged load and longitudinal and sorting samples shall be conducted on previously cleaned surfaces. If necessary, remove the sorting sample to a secured manual sorting area. The sorting sample may be placed on a clean table for sorting for the convenience of the sorting personnel. The sorting area shall be a previously cleaned, flat, level surface.

8.11 Position the storage containers around the sorting sample. Empty all containers from the sorting sample, such as

capped jars, paper bags, and plastic bags of their contents. Segregate each waste item and place it in the appropriate storage container.

8.12 In the case of composite items found in the waste, separate the individual materials where practical, and place the individual materials into the appropriate storage containers. Where impractical, segregate the composite items for classification by the crew chief according to the following order:

8.12.1 If there are many identical composite items (for example, plastic-sheathed aluminum electrical conductor), place them into the waste component containers corresponding to the materials present in the item, and in the approximate proportions according to the estimated mass fraction of each material in the item.

8.12.2 If there are only a few of the identical composite item, place them in the storage container corresponding to the material that comprises, on a weight basis, the majority of the item (for example, place bi-metal beverage cans in the ferrous container).

8.12.3 If composite items represent substantial weight percents of the sorting sample, a separate category should be established, for example, composite roofing shingles.

8.12.4 If none of the above procedures is appropriate, place the item(s) (or proportion it (them)) in the storage container labeled “other non-combustible” or “other combustible,” as appropriate.

8.13 Sorting continues until the maximum particle size of the remaining waste particles is approximately 0.5 in. (12.7 mm). At this point, apportion the remaining particles into the storage containers corresponding to the waste components represented in the remaining mixture. The apportionment shall be accomplished by making a visual estimate of the mass fraction of waste components represented in the remaining mixture.

8.14 Record the gross weights of the storage containers and of any waste items sorted but not stored in containers. The data sheet shown in Fig. 1 can be used to record both gross and tare weights.

8.15 After recording the gross weights, empty the storage containers and weigh them again, if appropriate. Re-weighing is important and necessary if the containers become moisture-laden, for example, from wet waste.

8.16 Clean the sorting site, as well as the load discharge area, of all waste materials.

9. Calculation

9.1 *Number of 200 to 300-lb (91 to 136-kg) Samples:*

9.1.1 The number of sorting samples (that is, vehicle loads) (*n*) required to achieve a desired level of measurement precision is a function of the component(s) under consideration and the confidence level. The governing equation for *n* is as follows:

$$n = (t^*s/e \cdot \bar{x})^2 \quad (1)$$

Waste Composition Data Sheet

Day/Date: _____ Collection Company: _____
 Site: _____ Vehicle Type: _____
 Weather: _____ Route No: _____
 Recorded by: _____

Component	Weight in Pounds		Percent of Total
	Gross	Tare	
Mixed Paper			
High Grade Paper			
Computer Printout			
Other Office Paper			
Newsprint			
Corrugated			
Plastic			
PET bottles			
HDPE bottles			
Film			
Other Plastic			
Food Waste			
Wood			
Other Organics			
Ferrous			
Cans			
Other Ferrous			
Aluminum			
Cans			
Foil			
Other Aluminum			
Glass			
Clear			
Brown			
Green			
Other Inorganics			
TOTALS			

NOTES: _____

Lab sample taken? Yes _____ No _____

FIG. 1 Waste Composition Data Sheet

where:

- t^* = student t statistic corresponding to the desired level of confidence,
- s = estimated standard deviation,
- e = desired level of precision, and
- \bar{x} = estimated mean.

9.1.1.1 All numerical values for the symbols are in decimal notation. For example, a precision value (e) of 20 % is represented as 0.2.

9.1.1.2 One sorting sample is chosen per vehicle load.

9.1.1.3 Suggested values of s and of \bar{x} for waste components are listed in Table 3. Values of t^* are given in Table 4 for 90 and 95 % levels of confidence, respectively.

9.1.2 Estimate the number of samples (n') for the selected conditions (that is, precision and level of confidence) and components using (Eq 1). For the purposes of estimation, select

TABLE 3 Values of Mean (\bar{x}) and Standard Deviation(s) for Within-Week Sampling to Determine MSW Component Composition⁴

Component	Standard Deviation(s)	Mean (\bar{x})
Newsprint	0.07	0.10
Corrugated	0.06	0.14
Plastic	0.03	0.09
Yard waste	0.14	0.04
Food waste	0.03	0.10
Wood	0.06	0.06
Other organics	0.06	0.05
Ferrous	0.03	0.05
Aluminum	0.004	0.01
Glass	0.05	0.08
Other inorganics	0.03	0.06
		1.00

⁴The tabulated mean values and standard deviations are estimates based on field test data reported for MSW sampled during weekly sampling periods at several locations around the United States.

TABLE 4 Values of t Statistics (t^*) as a Function of Number of Samples and Confidence Interval

Number of Samples, n	90 %	95 %
2	6.314	12.706
3	2.920	4.303
4	2.353	3.182
5	2.132	2.776
6	2.015	2.571
7	1.943	2.447
8	1.895	2.365
9	1.860	2.306
10	1.833	2.262
11	1.812	2.228
12	1.796	2.201
13	1.782	2.179
14	1.771	2.160
15	1.761	2.145
16	1.753	2.131
17	1.746	2.120
18	1.740	2.110
19	1.734	2.101
20	1.729	2.093
21	1.725	2.086
22	1.721	2.080
23	1.717	2.074
24	1.714	2.069
25	1.711	2.064
26	1.708	2.060
27	1.706	2.056
28	1.703	2.052
29	1.701	2.048
30	1.699	2.045
31	1.697	2.042
36	1.690	2.030
41	1.684	2.021
46	1.679	2.014
51	1.676	2.009
61	1.671	2.000
71	1.667	1.994
81	1.664	1.990
91	1.662	1.987
101	1.660	1.984
121	1.658	1.980
141	1.656	1.977
161	1.654	1.975
189	1.653	1.973
201	1.653	1.972
∞	1.645	1.960

from Table 4 the t^* value for $n = \infty$ for the selected level of confidence. Since the required number of samples will vary among the components for a given set of conditions, a

compromise will be required in terms of selecting a sample size, that is, the number of samples that will be sorted. The component that is chosen to govern the precision of the composition measurement (and therefore the number of samples required for sorting) is termed the “governing component” for the purposes of this method.

9.1.3 After determining the governing component and its corresponding number of samples (n_o), return to **Table 4** and select the student t statistic (t^*_{o}) corresponding to n_o . Recalculate the number of samples, that is, n' , using t^*_{o} .

9.1.4 Compare n_o to the new estimate of n , that is, n' , which was calculated for the governing component. If the values differ by more than 10 %, repeat the calculations given in **9.1.2** and **9.1.3**.

9.1.5 If the values are within 10 %, select the larger value as the number of samples to be sorted. Refer to **Appendix X1** for a sample calculation of n .

9.2 Component Composition:

9.2.1 The component composition of solid waste is reported on the basis of the mass fraction (expressed as a decimal) or percent of waste component i in the solid waste mixture. The reporting is on the basis of wet weight, that is, the weight of materials immediately after sorting.

9.2.2 The mass fraction of component i , mf_i , is defined and computed as follows:

$$mf_i = \frac{w_i}{\sum_{i=1}^j w_i} \quad (2)$$

where:

w_i = weight of component i and
 j = number of waste components.

In those cases in which a container is used to store and weigh the materials,

$$w_i = \text{gross weight} - \text{tare weight of container} \quad (3)$$

9.2.3 The percent of component i , P_i , is defined and computed as follows:

$$P_i = mf_i \times 100 \quad (4)$$

9.2.4 For the data analysis to be correct, the denominator of (Eq 2) must be unity, and

$$\sum_{i=1}^j P_i = 100 \quad (5)$$

9.3 The mean component composition for the one-week period is calculated using the component composition results from each of the analysis samples. The mean mass fraction of component i , \bar{mf}_i , is calculated as follows:

$$\bar{mf}_i = \frac{1}{n} \sum_{k=1}^n (mf_i)_k \quad (6)$$

and the mean percent of component i , \bar{P}_i , is calculated as follows:

$$\bar{P}_i = \frac{1}{n} \sum_{k=1}^n (P_i)_k \quad (7)$$

where:

n = number of samples.

10. Precision and Bias

10.1 A precision and bias statement cannot be made for this test method at this time. However, the committee is interested in conducting an interlaboratory test program and encourages interested parties to contact ASTM Headquarters.²

11. Keywords

11.1 composition; municipal solid waste; waste characterization

² ASTM Headquarters, 100 Barr Harbor Dr., West Conshohocken, PA 19428-2959.

APPENDIX

(Nonmandatory Information)

X1. EXAMPLE CALCULATION OF THE NUMBER OF SAMPLES FOR ANALYSIS

X1.1 Example Assumptions:

X1.1.1 Corrugated is selected as the governing component.

X1.1.2 A 90 % confidence level is selected.

X1.1.3 A precision of 10 % is desired.

X1.1.4 Therefore:

$$\begin{aligned} s &= 0.06 \text{ (from Table 3),} \\ \bar{x} &= 0.14 \text{ (from Table 3),} \\ e &= 0.10, \text{ and} \\ t^*(n=\infty) &= 1.645 \text{ (from Table 4).} \end{aligned}$$

Using (Eq 1):

$$n = [t^*s/(e \cdot \bar{x})]^2 \quad (X1.1)$$

$$= \left[\frac{1.645 (0.06)}{0.1 (0.14)} \right]^2$$

$$= 50$$

$$= n_o$$

Referring again to **Table 4**, for $n = 50$,

$$t^*_{90}(n = 50) = 1.677 \quad (\text{X1.2})$$

Since 52 (that is, n') is within 10 % of 50 (that is, n_0), 52 samples should be selected for analysis.

and,

$$\begin{aligned} n &= \left[\frac{1.677 (0.06)}{0.1 (0.14)} \right]^2 & (\text{X1.3}) \\ &= 52 \\ &= n' \end{aligned}$$

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org). Permission rights to photocopy the standard may also be secured from the Copyright Clearance Center, 222 Rosewood Drive, Danvers, MA 01923, Tel: (978) 646-2600; http://www.copyright.com/